

# MATERIAL SAFETY DATA SHEET

## Enviro-Safe™ POWER STEERING ENHANCER PLUS

### SECTION 1 – IDENTIFICATION

Company: Enviro-Safe Refrigerants, Inc.  
400 Margaret  
Pekin IL 61554  
309-346-1110

Product Name: Transmission Plus

**CHEMTREC – TOLL FREE 24 HOUR EMERGENCY TELEPHONE NUMBER  
1-800-424-9300**

### SECTION 2 – PHYSICAL DESCRIPTION AND/OR PROPERTIES

Appearance/Odor:	Red color; slight odor	Physical State:	Liquid
Odor Threshold:	N/A	Solubility in water:	Nonsoluble
Coeff. Water/Oil Dist:	N/A	Evaporation Rate:	<0.01
Melting point:	N/A	Boiling Point:	N/A
Vapor Density:	N/A	pH:	N/A
Vapor Pressure:	<1 @ 25°C	Specific Gravity:	1.06

### SECTION 3 – FIRE OR EXPLOSION HAZARD

**Auto Ignition Temperature:**

**Flashpoint:** 230° F (dmcc)

**Flammable Limit (LEL):** n/a

**Upper Flammable Limit (UEL):** n/a

**Extinguish Media:** foam, water fog, chemical, CO<sub>2</sub>

**Hazardous Combustion Products:** n/a

**Sensitivity to Static Discharge:** N.D.

**Explosion Data:** Not explosive

**Fire and Explosion Hazard:** Product in non-explosive and under normal use, non-flammable

### SECTION 4 – INGREDIENTS

<u>Hazardous Ingredients</u>	<u>%</u>	<u>Cas Number</u>	<u>LD50</u>	<u>P.E.L.</u>	<u>ACGIH TLV UNITS</u>
Trade Secret	01-10				
Dewaxed Heavy Paraffinic Oil	20-50	64742581, 64742627			
Dewaxed Light Paraffinic Oil	20-50	72623837 & others			
Organic Petroleum Hydrocarbons		64742-53-6		>3% 500 ppm	5mg/m <sup>3</sup>
Petroleum Lube Oil		64742-65-0		>3% 500 ppm	5 mg/m <sup>3</sup>

### SECTION 5 – REACTIVITY DATA

**Chemical Stability:** This material is chemically stable under normal condition

**Conditions To Avoid:** Avoid sparks, open flame or any source of ignition.

**Incompatible Materials:** Avoid contact with strong oxidizing agents such as chlorine, permanganates and dichromate's.

**Decomposition Products:**

**Hazardous Polymerization:** will not occur.

**Polymerization To Avoid:** non known

## SECTION 6 – HEALTH HAZARD

**Inhaled/Asphyxiant:** n/a

**Ingestion:** n/a

**Eye Contact:** Irritating if the liquid gets into eyes, flush with water.

**Skin Contact:** n/a

**Chronic:** n/a

## SECTION 7 - FIRST AID

**Inhaled:** Remove exposed person to fresh air.

**Eyes:** Flush eyes with water.

**Skin:** Wash with soap and water. Remove contaminated clothing

**Frostbite:** n/a

**Ingestion:** May cause nausea and vomiting, no long term effect.

## SECTION 8 - SAFE HANDLING

**Spills:** Contain spills with sand, earth or absorbent.

**Waste Disposal Method:** Dispose of product in accordance with local, county state, and federal regulations.

**Storage, Handling, Shipping:** Keep away from open flame and other ignition sources. Keep away from open food products. Do not store above 130° F.

**Other Precautions:** n/a

## SECTION 9 -PERSONAL PROTECTION

**Engineering Controls:** Exhaust if needed.

**Eyes:** Wear safety glasses or goggles.

**Gloves:** Neoprene or Buna-n

**Other protective clothing:** n/a

**Respiratory Protection:** Use NIOSH/OSHA approved respirator if TLV is exceeded.

## SECTION 10 -PREPARATION

Enviro-Safe Refrigerants, Inc., 400 Margaret, Pekin, IL 61554

Telephone: 309-346-1110

March 1, 1999  
Revised August 16, 2011

All information provided for this MSDS sheet by Enviro-Safe Refrigerants, Inc. is offered in good faith and is believed to be accurate to the best knowledge of the preparation analyst. The information contained in this document is based on documentation provided by the supplier and other documentation/information available at the date of preparation. Enviro-Safe does not guarantee the accuracy of this document and this information is offered without warranty, guarantee or liability on the part of the preparation analyst in good faith.