

SECTION 1: IDENTIFICATION

1.1. Product Identifier

Product Name: Enviro-Safe™ ProSeal for Small Systems

1.2. Intended Use of the Product

Use of the Substance/Mixture: A/C Sealant for small units

1.3. Name, Address, and Telephone of the Responsible Party

Company

Enviro-Safe Refrigerants, Inc.

400 Margaret Street

Pekin, IL 61554

309-346-1110

1.4. Emergency Telephone Number

Emergency Number : 1-800-424-9300

CHEMTREC – TOLL FREE 24 HOUR EMERGENCY TELEPHONE NUMBER

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the Substance or Mixture

Classification (GHS-US)

Simple Asphy

Flam. Gas 1 H220

Liquefied gas H280

2.2. Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US)



Signal Word (GHS-US)

: Danger

Hazard Statements (GHS-US)

: H220 - Extremely flammable gas

H280 - Contains gas under pressure; may explode if heated

Simple Asphy - May displace oxygen and cause rapid suffocation

Precautionary Statements (GHS-US)

: P210 - Keep away from heat, hot surfaces, open flames, sparks - No smoking.

P377 - Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

P381 - Eliminate all ignition sources if safe to do so.

P410+P403 - Protect from sunlight. Store in a well-ventilated place.

P501 - Dispose of contents/container according to local, regional, national, and international regulations.

2.3. Other Hazards

Other Hazards Not Contributing to the Classification: Contact with product may cause cold burns or frostbite.

Aquatic Acute 3

H402 - Harmful to aquatic life

P273 - Avoid release to the environment

2.4. Unknown Acute Toxicity (GHS-US)

No data available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
Petroleum gases, liquefied	(CAS No) 68476-85-7	97	Simple Asphy Flam. Gas 1, H220 Liquefied gas, H280

Enviro-Safe™ ProSeal for Small Systems

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	Classification (GHS-US)
Ethyl alcohol	(CAS No) 64-17-5	2.9999	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 Aquatic Acute 2, H401
Toluene	(CAS No) 108-88-3	0.0001	Flam. Liq. 2, H225 Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 2, H401

Full text of H-phrases: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of First Aid Measures

First-aid Measures General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid Measures After Inhalation: When symptoms occur: go into open air and ventilate suspected area. Immediately call a POISON CENTER or doctor/physician.

First-aid Measures After Skin Contact: If frostbite or freezing occurs, immediately flush with plenty of lukewarm water to GENTLY warm the affected area. Do not use hot water. Do not rub affected area. Get immediate medical attention.

First-aid Measures After Eye Contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.

First-aid Measures After Ingestion: Do not induce vomiting. Immediately call a POISON CENTER or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/Injuries: Gas can be toxic as a simple asphyxiant by displacing oxygen from the air. Refrigerated liquefied gas.

Contact with product may cause cold burns or frostbite.

Symptoms/Injuries After Inhalation: Asphyxiant gas.

Symptoms/Injuries After Skin Contact: May cause frostbite. May cause skin irritation.

Symptoms/Injuries After Eye Contact: Contact with the liquefied gas causes frostbite.

Symptoms/Injuries After Ingestion: Ingestion is an unlikely route of exposure for a gas.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention.

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Dry chemical powder, alcohol-resistant foam, carbon dioxide (CO₂).

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Flammable gas.

Explosion Hazard: Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.

Reactivity: Contains gas under pressure; may explode if heated. Reacts with strong oxidants causing fire and explosion hazard.

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion. Use water spray or fog for cooling exposed containers.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Use special care to avoid static electric charges. Keep away from open flames, hot surfaces and sources of ignition. No smoking. Do not get in eyes, on skin, or on clothing. Do not breathe gas.

6.1.1. For Non-emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Enviro-Safe™ ProSeal for Small Systems

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Emergency Procedures: Evacuate unnecessary personnel. Eliminate ignition sources.

6.1.2. For Emergency Responders

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Stop leak if safe to do so. Ventilate area.

6.2. Environmental Precautions

Avoid release to the environment.

6.3. Methods and Material for Containment and Cleaning Up

For Containment: Stop leak without risks if possible. Do not take up in combustible material such as: saw dust or cellulosic material.

Methods for Cleaning Up: Contact competent authorities after a spill.

6.4. Reference to Other Sections

See heading 8, Exposure Controls and Personal Protection.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Precautions for Safe Handling: Personnel should be trained to regularly inspect equipment such as pumps, hoses, and valves. Do not breathe gas. Ensure there is adequate ventilation. Close valve after each use and when empty. Open valve slowly to avoid pressure shock.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations. Cylinders should be stored upright with valve protection cap in place and firmly secured to prevent falling. Keep at temperatures below 52°C / 125°F.

Storage Conditions: Store in a dry, cool and well-ventilated place. Keep in fireproof place. Store locked up.

Incompatible Products: Heat sources. Oxidizers.

Special Rules on Packaging: Store in containers fitted with suitable release valve.

7.3. Specific End Use(s)

A/C Sealant.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

Petroleum gases, liquefied (68476-85-7)		
USA ACGIH	ACGIH TWA (ppm)	1000 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	1800 mg/m ³
USA NIOSH	NIOSH REL (TWA) (ppm)	1000 ppm
USA IDLH	US IDLH (ppm)	2100 ppm (10% LEL)
USA OSHA	OSHA PEL (TWA) (mg/m ³)	1800 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
Ethyl alcohol (64-17-5)		
USA ACGIH	ACGIH STEL (ppm)	1000 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	1900 mg/m ³
USA NIOSH	NIOSH REL (TWA) (ppm)	1000 ppm
USA IDLH	US IDLH (ppm)	3300 ppm (10% LEL)
USA OSHA	OSHA PEL (TWA) (mg/m ³)	1900 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
Toluene (108-88-3)		
USA ACGIH	ACGIH TWA (ppm)	20 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	375 mg/m ³
USA NIOSH	NIOSH REL (TWA) (ppm)	100 ppm
USA NIOSH	NIOSH REL (STEL) (mg/m ³)	560 mg/m ³
USA NIOSH	NIOSH REL (STEL) (ppm)	150 ppm
USA IDLH	US IDLH (ppm)	500 ppm
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm

Enviro-Safe™ ProSeal for Small Systems

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

USA OSHA	OSHA PEL (Ceiling) (ppm)	300 ppm
----------	--------------------------	---------

8.2. Exposure Controls

Appropriate Engineering Controls

: Alarm detectors should be used when toxic gases may be released. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure all national/local regulations are observed.

Personal Protective Equipment

: Gas mask. Protective goggles. Gloves. Protective clothing.



Materials for Protective Clothing

: Chemically resistant materials and fabrics.

Hand Protection

: Wear working gloves when handling gas containers.

Eye Protection

: Safety glasses.

Skin and Body Protection

: Wear suitable protective clothing.

Respiratory Protection

: Use a NIOSH-approved respirator or self-contained breathing apparatus whenever exposure may exceed established Occupational Exposure Limits.

Thermal Hazard Protection

: Wear cold insulating gloves.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

Physical State	: Gas
Appearance	: Colorless Liquid
Odor	: Amine Odor
Odor Threshold	: No data available
pH	: No data available
Relative Evaporation Rate (butylacetate=1)	: < 1
Melting Point	: No data available
Freezing Point	: No data available
Boiling Point	: 61.7 °C (143 °F)
Flash Point	: No data available
Auto-ignition Temperature	: No data available
Decomposition Temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor Pressure	: 117.74 hPa
Relative Vapor Density at 20 °C	: > 1 (Heavier than Air)
Relative Density	: 9.1 (water = 1)
Solubility	: No data available
Partition coefficient: n-octanol/water	: No data available
Viscosity	: No data available

9.2. Other Information

Gas group : Liquefied gas

SECTION 10: STABILITY AND REACTIVITY

- 10.1 Reactivity: Contains gas under pressure; may explode if heated. Reacts with oxidants causing fire and explosion hazard.
- 10.2 Chemical Stability: Stable under recommended handling and storage conditions (see section 7).
- 10.3 Possibility of Hazardous Reactions: Hazardous polymerization will not occur.
- 10.4 Conditions to Avoid: Direct sunlight. Extremely high or low temperatures. Open flame. Heat. Sparks.
- 10.5 Incompatible Materials: Heat. Strong oxidizers.
- 10.6 Hazardous Decomposition Products: Carbon oxides (CO, CO₂).

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information On Toxicological Effects

Acute Toxicity: Not classified

Petroleum gases, liquefied (68476-85-7)	
LC50 Inhalation Rat (mg/l)	658 mg/l/4h
Ethyl alcohol (64-17-5)	
LD50 Oral Rat	10470 mg/kg

Enviro-Safe™ ProSeal for Small Systems

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

LD50 Dermal Rat	20 ml/kg
LC50 Inhalation Rat (mg/l)	124.7 mg/l/4h
Toluene (108-88-3)	
LD50 Oral Rat	636 mg/kg
LD50 Dermal Rabbit	8390 mg/kg
LC50 Inhalation Rat (mg/l)	12.5 mg/l/4h

Skin Corrosion/Irritation: Not classified
 Serious Eye Damage/Irritation: Not classified
 Respiratory or Skin Sensitization: Not classified
 Germ Cell Mutagenicity: Not classified
 Carcinogenicity: Not classified

Toluene (108-88-3)	
IARC group	3

Reproductive Toxicity: Not classified
 Specific Target Organ Toxicity (Single Exposure): Not classified
 Specific Target Organ Toxicity (Repeated Exposure): Not classified
 Aspiration Hazard: Not classified
 Symptoms/Injuries After Inhalation: Asphyxiant gas.
 Symptoms/Injuries After Skin Contact: May cause frostbite. May cause skin irritation.
 Symptoms/Injuries After Eye Contact: Contact with the liquefied gas causes frostbite.
 Symptoms/Injuries After Ingestion: Ingestion is an unlikely route of exposure for a gas.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecology - General : Harmful to aquatic life.

Ethyl alcohol (64-17-5)	
LC50 Fish 1	9.468 (9.468 - 12.624) mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static]) converted from ml/l
EC50 Daphnia 1	9268 (9268 - 14221) mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC 50 Fish 2	100 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 2	2 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
Toluene (108-88-3)	
LC50 Fish 1	15.22 - 19.05 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	5.46 - 9.83 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
EC50 Other Aquatic Organisms 1	> 433 mg/l (Exposure time: 96 h - Species: Pseudokirchneriella subcapitata)
LC 50 Fish 2	12.6 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 2	11.5 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 Other Aquatic Organisms 2	12.5 mg/l (Exposure time: 72 h - Species: Pseudokirchneriella subcapitata [static])

12.2. Persistence and Degradability

Ethyl alcohol (64-17-5)	
Persistence and Degradability	Not established.

12.3. Bioaccumulative Potential

Petroleum gases, liquefied (68476-85-7)	
Log Pow	2.3
Ethyl alcohol (64-17-5)	
Log Pow	-0.32
Bioaccumulative Potential	Not established.
Toluene (108-88-3)	
Log Pow	2.65

12.4. Mobility in Soil No additional information available

12.5. Other Adverse Effects No additional information available

Enviro-Safe™ ProSeal for Small Systems

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, and international regulations.

Additional Information: Empty product containers may contain hazardous residue. Do not reuse empty containers without commercial cleaning or reconditioning.

SECTION 14: TRANSPORT INFORMATION

14.1 In Accordance with DOT

Proper Shipping Name : Consumer commodity
 DOT Symbols : D - Proper shipping name for domestic use only



14.2 In Accordance with IMDG

Proper Shipping Name : PETROLEUM GASES, LIQUEFIED
 Hazard Class : 2.1
 Identification Number : UN1075
 Label Codes : 2.1
 EmS-No. (Fire) : F-D
 EmS-No. (Spillage) : S-U
 Marine Pollutant : No



14.3 In Accordance with IATA

Proper Shipping Name : PETROLEUM GASES, LIQUEFIED
 Identification Number : UN1075
 Hazard Class : 2
 Label Codes : 2.1
 ERG Code (IATA) : 10L
 Marine Pollutant : No



SECTION 15: REGULATORY INFORMATION

15.1 US Federal Regulations

Enviro-Safe™ ProSeal for Small Systems	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Fire hazard Sudden release of pressure hazard
Petroleum gases, liquefied (68476-85-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Ethyl alcohol (64-17-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Toluene (108-88-3)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Listed on SARA Section 313 (Specific toxic chemical listings)	
RQ (Reportable quantity, section 304 of EPA's List of Lists) :	1000 lb
SARA Section 313 - Emission Reporting	1.0 %

15.2 US State Regulations

Ethyl alcohol (64-17-5)	
U.S. - California - Proposition 65 - Carcinogens List	WARNING: This product contains chemicals known to the State of California to cause cancer.
U.S. - California - Proposition 65 - Developmental Toxicity	WARNING: This product contains chemicals known to the State of California to cause birth defects.
Toluene (108-88-3)	
U.S. - California - Proposition 65 - Developmental Toxicity	WARNING: This product contains chemicals known to the State of California to cause birth defects.
U.S. - California - Proposition 65 - Reproductive Toxicity - Female	WARNING: This product contains chemicals known to the State of California to cause (Female) reproductive harm.

Enviro-Safe™ ProSeal for Small Systems

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Petroleum gases, liquefied (68476-85-7)

U.S. - Connecticut - Hazardous Air Pollutants - HLVs (30 min)
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (8 hr)
U.S. - Delaware - Accidental Release Prevention Regulations - Sufficient Quantities
U.S. - Delaware - Accidental Release Prevention Regulations - Threshold Quantities
U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities
U.S. - Idaho - Occupational Exposure Limits - TWAs
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 1 and 2
U.S. - Massachusetts - Oil & Hazardous Material List - Reportable Quantity
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 1 and 2
RTK - U.S. - Massachusetts - Right To Know List
U.S. - Michigan - Occupational Exposure Limits - TWAs
U.S. - Minnesota - Hazardous Substance List
U.S. - Minnesota - Permissible Exposure Limits - TWAs
U.S. - New Jersey - Discharge Prevention - List of Hazardous Substances
U.S. - New Jersey - Environmental Hazardous Substances List RTK
- U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - New Jersey - Special Health Hazards Substances List
U.S. - New Jersey - TCPA - Extraordinarily Hazardous Substances (EHS)
U.S. - New York - Occupational Exposure Limits - TWAs
U.S. - Ohio - Accidental Release Prevention - Threshold Quantities
U.S. - Oregon - Permissible Exposure Limits - TWAs RTK
- U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Tennessee - Occupational Exposure Limits - TWAs
U.S. - Texas - Effects Screening Levels - Long Term and Short Term
U.S. - Vermont - Permissible Exposure Limits - TWAs
U.S. - Washington - Permissible Exposure Limits - STELs and TWAs

Ethyl alcohol (64-17-5)

U.S. - Connecticut - Hazardous Air Pollutants - HLVs (30 min)
U.S. - Connecticut - Hazardous Air Pollutan
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs)
U.S. - Idaho - Occupational Exposure Limits - TWAs
U.S. - Maine - Chemicals of High Concern
U.S. - Massachusetts - Allowable Ambient Limits (AALs)
U.S. - Massachusetts - Allowable Threshold Concentrations (ATCs)
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 1 and 2
U.S. - Massachusetts - Oil & Hazardous Material List - Reportable Quantity
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 1 and 2
RTK - U.S. - Massachusetts - Right To Know List
U.S. - Massachusetts - Threshold Effects Exposure Limits (TELEs)
U.S. - Michigan - Occupational Exposure Limits - TWAs
U.S. - Minnesota - Chemicals of High Concern
U.S. - Minnesota - Hazardous Substance List
U.S. - Minnesota - Permissible Exposure Limits - TWAs
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual
RTK - U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - New Jersey - Special Health Hazards Substances List
U.S. - New York - Occupational Exposure Limits - TWAs
U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 1-Hour
U.S. - Oregon - Permissible Exposure Limits - TWAs RTK
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Tennessee - Occupational Exposure Limits - TWAs

Enviro-Safe™ ProSeal for Small Systems

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

U.S. - Texas - City of Austin - Aerosol Paint and Glue Restrictions
U.S. - Texas - Effects Screening Levels - Long Term and Short Term
U.S. - Vermont - Permissible Exposure Limits - TWAs
U.S. - Washington - Permissible Exposure Limits – STELs and TWAs

Toluene (108-88-3)

U.S. - California - Priority Toxic Pollutants - Human Health Criteria
U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL)
U.S. - California - SCAQMD - Toxic Air Contaminants - Non-Cancer Acute
U.S. - California - SCAQMD - Toxic Air Contaminants - Non-Cancer Chronic
U.S. - California - Toxic Air Contaminant List (AB 1807, AB 2728)
U.S. - Colorado - Groundwater Quality Standards
U.S. - Colorado - Hazardous Wastes - Discarded Chemical Products, Off-Specification Species, Container and Spill Residues
U.S. - Colorado - Primary Drinking Water Regulations - Maximum Contaminant Level Goals (MCLGs)
U.S. - Colorado - Primary Drinking Water Regulations - Maximum Contaminant Levels (MCLs)
U.S. - Connecticut - Drinking Water Quality Standards - Maximum Contaminant Levels
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (30 min)
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (8 hr)
U.S. - Connecticut - Volatile Substances
U.S. - Connecticut - Water Quality Standards - Consumption of Organisms Only
U.S. - Connecticut - Water Quality Standards - Consumption of Water and Organisms
U.S. - Connecticut - Water Quality Standards - Health Designations
U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities
U.S. - Florida - Drinking Water Standards - Volatile Organic Contaminants - Maximum Contaminant Levels (MCLs)
U.S. - Florida - Essential Chemicals List
U.S. - Georgia - Drinking Water - Maximum Contaminant Levels (MCLs)
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs)
U.S. - Idaho - Occupational Exposure Limits - Acceptable Maximum Peak Above the Ceiling Concentration for an 8-Hour Shift
U.S. - Idaho - Occupational Exposure Limits - Ceilings and TWAs
U.S. - Illinois - Toxic Air Contaminants
U.S. - Louisiana - Reportable Quantity List for Pollutants
U.S. - Maine - Air Pollutants - Hazardous Air Pollutants
U.S. - Maine - Chemicals of High Concern
U.S. - Maryland - Surface Water Quality Standards - Consumption of Organisms Only
U.S. - Maryland - Surface Water Quality Standards - Consumption of Water and Organisms
U.S. - Massachusetts - Allowable Ambient Limits (AALs)
U.S. - Massachusetts - Allowable Threshold Concentrations (ATCs)
U.S. - Massachusetts - Drinking Water - Maximum Contaminant Levels (MCLs)
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 1 and 2
U.S. - Massachusetts - Oil & Hazardous Material List - Reportable Quantity
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 1 and 2 RTK –
U.S. - Massachusetts - Right To Know List
U.S. - Massachusetts - Threshold Effects Exposure Limits (TELEs)
U.S. - Massachusetts - Toxics Use Reduction Act
U.S. - Michigan - Occupational Exposure Limits – STELs and TWAs
U.S. - Michigan - Polluting Materials List
U.S. - Minnesota - Chemicals of High Concern
U.S. - Minnesota - Groundwater Health Risk Limits
U.S. - Minnesota - Hazardous Substance List
U.S. - Minnesota - Permissible Exposure Limits – STELs and TWAs
U.S. - Missouri - Drinking Water - Maximum Contaminant Levels (MCLs)
U.S. - Nebraska - Drinking Water - Maximum Contaminant Levels (MCLs)
U.S. - New Hampshire - Drinking Water - Maximum Contaminant Levels (MCLs)
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual

Enviro-Safe™ ProSeal for Small Systems

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

U.S. - New Jersey - Discharge Prevention - List of Hazardous Substances
U.S. - New Jersey - Environmental Hazardous Substances List
U.S. - New Jersey - Primary Drinking Water Standards - Maximum Contaminant Levels - MCLs RTK –
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - New Jersey - Special Health Hazards Substances List
U.S. - New Jersey - Water Quality - Ground Water Quality Criteria
U.S. - New Jersey - Water Quality - Practical Quantitation Levels (PQLs)
U.S. - New Mexico - Water Quality - Standards for Ground Water of 10,000 mg/L TDS Concentration or Less
U.S. - New York - Occupational Exposure Limits - TWAs
U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances
U.S. - North Carolina - Control of Toxic Air Pollutants
U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 8-Hour
U.S. - North Dakota - Hazardous Wastes - Discarded Chemical Products, Off-Specification Species, Container and Spill Residues
U.S. - North Dakota - Water Quality Standards - Human Health Value for Class III
U.S. - North Dakota - Water Quality Standards - Human Health Value for Classes I, IA, II
U.S. - Oregon - Permissible Exposure Limits - Ceilings
U.S. - Oregon - Permissible Exposure Limits – STELs and TWAs
U.S. - Pennsylvania - Drinking Water - Maximum Contaminant Levels (MCLs)
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Rhode Island - Air Toxics - Acceptable Ambient Levels - 1-Hour
U.S. - Rhode Island - Air Toxics - Acceptable Ambient Levels - Annual
U.S. - Rhode Island - Water Quality Standards - Acute Freshwater Aquatic Life Criteria
U.S. - Rhode Island - Water Quality Standards - Chronic Freshwater Aquatic Life Criteria
U.S. - Rhode Island - Water Quality Standards - Human Health Criteria for Consumption of Aquatic Organisms Only
U.S. - Rhode Island - Water Quality Standards - Human Health Criteria for Consumption of Water and Aquatic Organisms
U.S. - South Carolina - Maximum Contaminant Levels (MCLs)
U.S. - South Carolina - Toxic Air Pollutants - Maximum Allowable Concentrations
U.S. - South Carolina - Toxic Air Pollutants - Pollutant Categories
U.S. - Tennessee - Occupational Exposure Limits – STELs and TWAs
U.S. - Texas - City of Austin - Aerosol Paint and Glue Restrictions
U.S. - Texas - Drinking Water Standards - Maximum Contaminant Levels (MCLs)
U.S. - Texas - Effects Screening Levels - Long Term and Short Term
U.S. - Utah - Drinking Water - Maximum Contaminant Levels (MCLs)
U.S. - Vermont - Hazardous Waste - Hazardous Constituents

Enviro-Safe™ ProSeal for Small Systems

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

U.S. - Vermont - Permissible Exposure Limits – STELs and TWAs
U.S. - Virginia - Water Quality Standards - Public Water Supply Effluent Limits
U.S. - Virginia - Water Quality Standards - Surface Waters Not Used for the Public Water Supply Effluent Limits
U.S. - Washington - Dangerous Waste - Dangerous Waste Constituents List
U.S. - Washington - Dangerous Waste - Discarded Chemical Products List
U.S. - Washington - Permissible Exposure Limits – STELs and TWAs
U.S. - West Virginia - Water Quality - Groundwater Standards - Ceiling Concentrations
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 25 Feet to Less Than 40 Feet
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 40 Feet to Less Than 75 Feet
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 75 Feet or Greater
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights Less Than 25 Feet

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision date : 09/02/2014

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Asp. Tox. 1	Aspiration hazard Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Gas 1	Flammable gases Category 1
Flam. Liq. 2	Flammable liquids Category 2
Liquefied gas	Gases under pressure Liquefied gas
Repr. 2	Reproductive toxicity Category 2
Simple Asphy	Simple Asphyxiant
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H220	Extremely flammable gas
H225	Highly flammable liquid and vapor
H280	Contains gas under pressure; may explode if heated
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness
H361	Suspected of damaging fertility or the unborn child
H373	May cause damage to organs through prolonged or repeated exposure
H401	Toxic to aquatic life
H402	Harmful to aquatic life

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

SDS US (GHS HazCom)