

## ALTERNATE A/C RECHARGE KIT

### DIRECTIONS:

*It is advised to follow the manufacturer's instruction for servicing you air conditioner.*

*This information is only to be used as a guideline. If you do not know how to service your air conditioning system, it is advised that you contact a professional.*

NOTE: The low pressure port is generally the big line coming out of the air conditioning unit.

1. Do NOT charge into vacuum state.
2. Connect the product to a tap and gauge.
3. Connect the tap and gauge to the low side port (big line on a/c system).
4. Turn on the A/C system (make sure it is running)
5. Do NOT overfill the A/C system.
6. Fill to manufacturer specifications
7. When the system is filled to the proper pressure, disconnect the tap and gauge for the low side port.
8. If technical assistance is needed, you may email Enviro-Safe at: [envirosafe2000@hotmail.com](mailto:envirosafe2000@hotmail.com) or call 888-913-1110 M-F 8:00 a.m. – 5:00 p.m. cst

NOTE: There is more product in the kit than is needed for most auto a/c systems.

The **stop leak** will seal the leak in o-ring and seal.

The **oil charge** will inject 2 ounces of oil and 2 ounces of refrigerant into the system.

**Oil Charge** is provided . . . use ONLY if needed.

Refrigerant with dye will give the refrigerant a fluorescent dye that is visible with a black light and assist in finding leaks in the system.